

Appln Serial No. 10/088,717  
Amendment dated March 1, 2005

**Amendments to the Claims:**

The following listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1 to 16 (cancelled)

17. (currently amended) A washing device for a car wash unit, the washing device mounted on a shaft and comprising:

at least two groups a plurality of substantially transverse spaced bristle elements and two groups of strip wash elements on a periphery of the washing device that are the two groups of bristle elements and the two groups of strip wash elements being transversely spaced apart and arranged in an alternating manner such that a group of bristle elements is next to a group of strip wash elements,

wherein the bristle wash elements have a diameter greater length than the wash strip elements.

18. (original) The washing device of claim 17 wherein the strip wash elements are made of a plastic foam.

19. (original) The washing device of claim 18 wherein the plastic foam is a closed-pore polyethylene foam.

20. (original) The washing device of claim 17 wherein the strip wash elements are made of a fiber material.

21. (original) The washing device of claim 20 wherein the fiber material is cloth or felt.

Appln Serial No. 10/088,717  
Amendment dated March 1, 2005

22. (original) The washing device of claim 17 wherein the strip wash elements comprise individual thin strips or cloths with slits.
23. (original) The washing device of claim 17 wherein the bristle and strip wash elements are arranged in an alternating manner in a circumferential direction.
24. (original) The washing device of claim 17 wherein the bristle and strip wash elements are arranged in an alternating manner in an axial direction.
25. (original) The washing device of claim 17 further comprising groove rings and wherein the bristle and strip wash elements are secured to the groove rings and wherein the bristle wash elements are configured as bristle tufts.
26. (original) The washing device of claim 25 wherein the bristle wash elements are made of polyethylene, polyamide, or polypropylene.
27. (original) The washing device of claim 17 wherein the washing device is a scrub brush and the bristle and strip wash elements are arranged in a lower region of the scrub brush rotating about a substantially vertical axis.
28. (original) The washing device of claim 17 wherein the washing device is a scrub brush and the bristle and strip wash elements are arranged on two end regions of the scrub brush rotating about a substantially horizontal axis.
29. (original) The washing device of claim 17 further comprising groove rings arranged in twist-lock manner on the shaft and wherein the bristle and strip wash elements are secured to the groove rings.

Appln Serial No. 10/088,717  
Amendment dated March 1, 2005

30. (original) The washing device of claim 17 wherein the washing device has upper and lower regions and the plurality of alternating bristle and strip wash elements are located in the lower region.
31. (original) The washing device of claim 17 further comprising groove rings arranged on the shaft and wherein at least one of the groove rings includes twelve rows of bristle wash elements and twelve rows of strip wash elements arranged in uniform alternation and distributed about the groove ring circumference.
32. (original) The washing device of claim 17 wherein the bristle wash elements in a fully extended condition are around 5 cm longer than the strip wash elements.
33. (original) The washing device of claim 17 wherein the bristle wash elements are fastened in radial openings on the washing device and arranged between axial grooves that accommodate the strip wash elements.
34. (original) The washing device of claim 33 wherein the radial openings are on the shaft.
35. (original) The washing device of claim 17 wherein the bristle wash elements and the strip wash elements are each arranged in bundles and are uniformly distributed peripherally and axially, and the bundles are secured in radial openings on the washing device.
36. (original) The washing device of claim 35 wherein at least some of the radial openings contain both bristle and strip wash elements.
37. (original) The washing device of claim 35 wherein the radial openings are on the shaft.

Appln Serial No. 10/088,717  
Amendment dated March 1, 2005

38. (original) The washing device of claim 17 wherein each bristle wash element comprises a row of bristle tufts.